WS-1

The 7x7 forward-facing 6-pack must provide a pole and necessary

power components to accommodate power and low-voltage from the 12' ceiling. The 6-pack must

- include: (12) 42"w x 42"h non powered panels
 - (6) 42"w x 16"h clear glass stacking panels
 - (6) 42"w x 64"h powered panels (3 base raceway duplex receptacles per workstation)
 - (6) 24"x84" HPL worksurfaces with cord drop or 2 grommets/

Notched openings

(6) 24"x60" HPL worksurfaces with cord drop or 2 grommets/

Notched openings

- (6) 24"d metal worksurface end support panels Include additional worksurface support as needed
- (6) 42"w metal locking flipper door overheads with tasklight
- (6) 42"w metal shelf
- (6) 24"d locking metal fixed file/files
- (6) 18"d metal locking mobile box/file with cushion top and pencil travs
- (6) 42"w tackboards
- (6) 42"w slat rail tiles
- (6) pencil cups: plastic or metal
- (6) pencii cups; piastic or metai
- (6) diagonal sorting trays; plastic or metal

(12) paper trays; plastic or metal Note: Task chair shown for reference only

Note: refer to RFP Section A.3.c for panel height and width variance




WS-5

The pinwheel must provide a pole and necessary power components to accommodate power and low-voltage from the 12' ceiling. The assembly must include:

- (4) 42"w x 42"h powered panels (1 base raceway duplex receptacle per panel/station)
- (4) 42"w x 16"h clear glass stacking panels
- (2) 24"x60" HPL worksurfaces with cord drop or 1 grommet/Notched opening
- (2) Metal Open, O-leg, or H-leg supports
 Include additional worksurface support as needed
- (2) 24"x60" electric height adjustable tables with 1 center grommet and 1 clamp-mount plug-in power/data modules with 3 receptacles and 1 data blank
- (4) 18"d metal locking mobile box/files with cushion top and pencil tray

Note: Task chairs shown for reference only Note: refer to RFP Section A.3.c for panel height and width variance





WS-10

The hoteling style 4-pack must provide a pole and necessary power components to accommodate power and low-voltage from the 12' ceiling. The assembly must include:


- (6) 42"w x 42"h non powered panels
- (2) 42"w x 42"h powered panels (1 base raceway duplex receptacle per workstation)
- (2) 30"w x 42"h powered panels (1 base raceway duplex receptacle per workstation)
- (8) 42"w x 16"h clear glass stacking panels
- (2) 30"w x 16"h clear glass stacking panels
- (4) 30"d x72"w HPL worksurfaces with cord drop or 2 grommets/Notched openings

2 grommets;

fully supported by cantilevers

- (4) 18"d metal locking mobile box/file with cushion top and pencil tray
- Note: Task chairs shown for reference only

Note: refer to RFP Section A.3.c for panel height and width variance






GC-1

The 7x7 glass cubicle 3-pack must provide a pole and necessary power components to accommodate power and low-voltage from the 12' ceiling. The assembly must include:

- (6) 42" w x 64"h powered panels (1 base raceway duplex receptacle per workstation)
- (8) 42"w x 64"h non powered panels
- (3) 42"w x 80"w locking sliding clear glass door
- (3) 42"w x 80"h clear glass panel
- (14) 42"w x 16"h clear glass stacking panels
- (3) 30"d x72"w electric height adjustable HPL tables with cord drop or 1 center grommet/notched opening and 1 clamp-mount plug-in power/data modules with 3 receptacles and 1 data blank
- (3) 18"d metal locking mobile box/file with cushion top and pencil tray

Note: Task chairs shown for reference only Note: refer to RFP Section A.3.c for panel height and width variance





OF-1

The private office assembly must include:

(1) 30"d x72"w key/wedge or jetty HPL worksurface supported by metal Open, O-leg, or H-legs

(1) 18"d x48"w bridge HPL worksurface

(1) 24"d x72"w HPL worksurface with cord drop or 2 grommets/Notched openings supported by full metal or laminate end support panels

(1) 72"w metal locking flipper door overhead with tasklight

(1) 24"d metal mobile box/file with cushion top; locking; pencil tray

(1) 18"d x 30"w metal locking fixed file/file

(1) 36"w tackboard

(1) 36"w slat rail tile


(1) plug-in clamp mount power/data centers with 3

receptacles and 1 data blank each (1) pencil cup; plastic or metal

(1) diagonal sorting tray; plastic or metal

(2) paper trays; plastic or metal Note: Task chairs shown for reference only

Note: Side chair shown for reference only






OF-3

The wood veneer executive office assembly must include:

- (1) 36"d x72"w wood breakfront desk with full modesty panel and locking box/box/file pedestal; 1 grommet
- (1) 24"d x 48"w wood bridge with full modesty and center drawer; 1 grommet
- (1) 24"d x 72"w wood credenza with full modesty panel and locking file/file pedestal; 1 grommet
- (1) 24"d x 36"w wood veneer locking 2-drawer lateral file
- (1) 72"w wood veneer locking set-on highback organizer with glass-insert doors, 72"w tackboard, and tasklight
- (2) 4-leg open arm wood frame upholstered seat/back executive side chairs

Note: Task chairs shown for reference only



CA-4


The collaborative storage assembly must include:

- (6) 18"d x 36"w metal locking 3-drawer lateral files with laminate common top
- (1) 36"d x 72"w HPL laminate top with HPL laminate full end panels; no power/data accommodations needed
- (4) bar-height polypropylene seat/back armless stools with 4-leg or sled base frame



EN-1

- (1) $30^{\prime\prime} d \times 60^{\prime\prime} w$ HPL laminate table top with metal T-leg supports
- (4) CH-2 Side chairs with fixed loop arm, upholstered seat and back, and a 4-leg frame with casters



EN-2

- (4) Lounge chairs with fully upholstered arms, seat, and back. Mobile chair on casters with pull bar is ideal.
- (1) Approximately 24"w x 48"d x 16"-18"h coffee table with steel base and HPL laminate top



CH-1

Mid-Back Task Chair with mesh back and waterfall upholstered seat. Chair must also include height adjustable arms, swivel-tilt adjustment, pneumatic height adjustment, lumbar support, and 5 star metal painted or epoxy coated caster base suitable for hard and soft flooring.




CH-2

Side chair with fixed loop arm, upholstered seat and back, and a 4-leg frame with casters



CA-13

- (7) Upholstered square ottomans with metal leg
- (1) square laminate table with metal leg
- (1) 48"w armless fully upholstered seat/back banquet seating with metal leg



TT-1

24"d x 72"w HPL laminate top training table with metal C-leg or T-leg supports on casters. Nesting table must include flip-top mechanism and basic wire management.



CT-1

 48° d x 144° w conference table with HPL laminate top and metal post support legs. Table must include two cutouts to accommodate two power/data modules. Each module must provide 4 power receptacles and 4 data ports. Table must include wire management to completely conceal power and data cabling from the underside of the table to the floor.



LO-1

6-cubby locker unit with metal or HPL laminate chassis and laminate door fronts. Doors must be individually locking with the use of a key/core. Ideal size per cubby is approximately 18"d x 18"w x 18"h with a depth and height variance of +/- 3", and a width variance of +/- 6". Each cubby must include one adjustable metal shelf.

